

**ITEM # ZB5AZ102, BASE & CONTACT BLOCK**

Plastic Base with Contact Block



Specifications

|  |                           |
|--|---------------------------|
| <b>Product Description</b>                 | Base & Contact Block      |
| <b>Ampere Rating</b>                       | 10A                       |
| <b>Terminal Type</b>                       | Screw Clamp               |
| <b>Wire Range</b>                          | min: 1x0.22; max: 2x16AWG |
| <b>Tightening Torque</b>                   | 0.8 Nm                    |
| <b>Light Module Electrical Consumption</b> | n/a                       |
| <b>CE</b>                                  | Yes                       |
| <b>RoHS</b>                                | Yes                       |
| <b>Contact Configuration</b>               | 1 N.C.                    |
| <b>Contact Material</b>                    | Silver Alloy              |
| <b>Light Module Supply Voltage</b>         | n/a                       |
| <b>Light Module Type</b>                   | n/a                       |
| <b>Light Module Voltage</b>                | n/a                       |
| <b>Utilization Category</b>                | AC-15; DC-13              |

|                |                       |
|----------------|-----------------------|
| <b>Used On</b> | ZB5 Plastic Operators |
|----------------|-----------------------|

|                    |          |
|--------------------|----------|
| <b>Application</b> | standard |
|--------------------|----------|